

325TA | Solid-Side Tandem Axle Utility

Shown with Optional Ramp Gate

GVWR: 7,000 lbs
BED LENGTHS: 12'-18'
BED WIDTH: 83"



SEALED WIRING HARNESS
with molded 7-way plug

SIDES
Solid panel sides.

FLOOR
2" Treated Lumber, installed AFTER painting to ensure no framing is left unfinished. Floor is secured with 5/16" screws and bolt-on board caps.

TIE DOWNS
4 U-Bolt Tie Down points welded inside

OPTIONAL RAMP GATE
48" Reinforced, Spring Assisted Ramp Gate with ergonomic lift handles.
(Tractor Gate or Rear Slide-In Ramps also available)

BOXED TAIL LIGHTS
Lights are waterproof, rubber-mounted, and the mounting box is raised to the top-rail for increased protection and visibility.

JACK
2000 lb Top-Wind Jack, Bolted-on with Foot

COUPLER
2" - 7000 lb Capacity Sleeve-Lock

FULL WRAP TONGUE
The most vulnerable part of any trailer frame is the midsection in front of the axles. All Diamond C tandem axle trailers have a full-wrap tongue which reinforces the frame all the way to the front fender brace.

RUBBER-MOUNTED ALL LED LIGHTS

FRAME
12 Ga. X 15" Integral Sides

CROSS MEMBERS
3" x 2" x 3/16" Angle

DEXTER AXLE
3500 lb E-Z Lube, for quick and easy lubrication, with 1 Electric Brake

TIRES
ST205/75D15
15" X 5 Hole Wheels



Diamond C uses road-tested DuPont polyurethanes that provide the trailers with a long-lasting, rugged, and beautiful finish.

Specifications, standard features, options, components, and colors are subject to change without notice. Some features may be subject availability, delays, or discontinuance.

Standard Premium Dupont Paint Colors
Custom colors available upon request.

